

# Paracol Miroseal MS

1/1

## DESCRIPTION

**PARACOL MIROSEAL MS** is a solvent free, elastic adhesive with very high initial tack, for bonding mirrors.

## APPLICATIONS

Forms a permanent water-tight and weatherproof bond to many surfaces such as glass, aluminium, etc.. For fixing special kinds of mirrors a test is recommended.

## SURFACES

The surfaces must be clean, dry, sound and free of dust.

## METHOD OF USE

Heavy mirrors should be supported for several hours. The adhesive must be applied in vertical lines of max. 15 mm wide. Between the mirror and the wall a space of at least 5 mm must be respected. Avoid humid surfaces, humid rooms, and big differences in temperature, aggressive air parts and chemical influences.

## PACKING

25 cartridges of 290 ml.

## SHELF-LIFE

**PARACOL MIROSEAL MS** can be stored 12 months if kept in original hermetically closed bag - 6 months when opened. Store in a dry and cool place between +5°C and +25°C.

## PRECAUTIONS

Consult our health and safety data sheet.

## COLOURS

Grey

## PROPERTIES

### Unvulcanised rubber

Type of sealant	MS-polymer
Vulcanising system	Vulcanising through moisture in the air
Skin forming time (23°C and 50% R.H.)	25 min
Vulcanisation rate (23°C and 50% R.H.)	2 mm/24 hrs
Density (ISO 1183)	1.52 g/ml

### Vulcanised rubber

Shore A hardness (ISO 868)	50
Modulus at break (ISO 8339-40)	1.75 N/mm <sup>2</sup>
% elongation at break (ISO 8339-40)	230 %
Temperature resistance	-40°C - + 90°C

012012

The data on this sheet have been drafted according to the last state of the laboratory data. Technical characteristics can be changed or adapted. We are not responsible in case of incompleteness. Before usage, one needs to ensure that the product is suitable for its application. Therefore, tests are necessary. Our general conditions apply.