

Paracol Tuile

1/2

DESCRIPTION

PARACOL TUILE is a one-component adhesive based on special elastomers, used for flexible bonding of pantiles.

APPLICATION TEMPERATURE

+5°C - +40°C.

INSTRUCTIONS FOR USE

The surfaces have to be clean and dry. If necessary use a primer (DL 783)
It is advised to test adhesion before starting the work. If necessary contact our technical service.

CLEANING

Before curing:

- a) tools : with white spirit or acetone
- b) surfaces: with **Parasilico Cleaner**

After curing:

Remove as much as possible mechanically.

COLOURS

Red stone colour. Other colours are on demand
(min. 75 cartridges)

SHELF-LIFE

Min.12 months in the original and hermetically closed packing under normal climatologically conditions.

PACKAGING

25 cartridges 310 ml/box – 48 boxes/pallet
20 bags 600 ml/ box – 36 boxes /pallet

APPLICATION

With a manual or pneumatic gun.

SAFETY

Please consult our safety data sheet.

TECHNICAL APPROVALS

CEBTP :

Report n° B252.3.078/1 : tests according to NF P 85-611 « adhesives for bonding pantiles ».

PROPERTIES

Unvulcanised rubber

Type of sealant	Elastomers
Vulcanising system	Chemical reaction through moisture in the air
Skin forming time (23°C and 50% R.H.)	15 à 20 min
Vulcanisation rate (23°C and 50% R.H.)	3 mm/24 h
Density (ISO 1183)	1,35 g/ml

Vulcanised rubber

Shore A hardness (ISO 868)	25
Elastic recovery (ISO 7389)	> 90%
Modulus at 100 % elongation (ISO 8340)	0,39 N/mm ²
% elongation at break (ISO 8339)	290 %
Temperature resistance	-50°C - + 100°C