



Paracryl Parafill

DESCRIPTION

PARACRYL PARAFILL is a ready to use product for the filling of cracks, joints and gaps of max. 50 mm deep and 50 mm wide. The product can be applied in one single movement. Larger joints have to be filled in several steps with 1 day in between.

PARACRYL PARAFILL does not sag, shrink or crack and is paintable after a few minutes, but ideal is after +/- 2 hours. Layers of 4 to 25 mm give the best result.

When dry, **PARACRYL PARAFILL** can be abraded by abrasive paper (after 1 day).

APPLICATION

PARACRYL PARAFILL has to be painted twice when used outdoors.

PARACRYL PARAFILL has an extremely strong adhesion on porous materials such as stone, concrete, plaster, wood, etc.

Remarks: **PARACRYL PARAFILL** cannot be used on synthetic, metal and permanently humid surfaces.

METHOD OF USE

Pots of 1 l . 5 l . 10 l:

Stir before use. Apply the product on a clean and dry surface with a spatula and smooth afterwards.

When too dry, add one coffee spoon of water for each 250 ml **PARAFILL** and stir until a smooth paste is obtained.

SECURITY

Keep out of reach of children.

PACKING

1 liter . 5 liter . 10 liters

SHELF-LIFE

12 months in unopened packing. Keep away from frost.

TECHNICAL CHARACTERISTICS

Density pot	0,45 g/ml
Base	special acryl polymers
Consistency	thixotropic paste
Possibility to abrase	after 1 day
Paintable	after a couple of minutes (ideal after +/- 2 hours)
Shrinkage	nil
Open time	10 à 15 minutes
Processing temperature	+5°C - +35°C