

	CONSTRUCTION	500	600	700	800	TRANSPARENT	GLAZING	MARINE-PARQUET	ZINC	LOW MODULUS
MS POLIMERI & SIGILANȚI HIBRIZI - Parabond										
CARACTERISTICI GENERALE										
Elasticitate	••	•	••	••	••	•	••	••	••	•••
Sanitar/Zone umede	•	•	•	•	•	•	-	•	•	•
Rezistență la UV	••	••	••	••	••	••	•••	••	••	•
Lipire	••	•••	•••	•••	•••	••	-	••	•••	••
Vopsire	••	••	••	••	••	••	•••	••	••	••
Aplicabil pe suprafețe umede	••	••	••	••	••	••	••	••	••	••
UTILIZARE										
Piatră naturală	•••/••	••	••	••	••	••	-	••	••	••
Suprafețe alcaline (beton, ciment, ...)	•••	•••	•••	•••	•••	•••	-	•••	•••	•••
Cărămidă	•••	••	••	••	••	••	-	•	•	•••
BCA	•	•	•	•	•	•	•	•	•	•••
Lemn	•••	•••	•••	•••	•••	•••	•••	•••	•	•••
Sticlă	-	-	-	•	•	•	•••	•	•	•
Metale (Aluminiu, zinc, plumb, cupru)	•••	•••/••	•••/••	•••/••	•••/••	•••/•	•••	•••/•	•••	•••
Țigle	•••	•••	•••	•••	•••	•••	•••	•••	•••	••
Materiale plastice (PVC, ABS, Poliester)	•••	•••	•••	•••	•••	•••	•••	•	•	••
Polycarbonat, Poliacrilat	•	•	•	•	•	•	•	•	•	•
Baie & Duș	••	••	••	••	••	••	•	••	•	••
Suprafețe poroase	•••	•••	•••	•••	•••	•••	•••	•••	•••	•••
Pereți din gips-carton	••	••	••	••	••	••	••	••	•	•••

Foarte potrivit	•••
Potrivit	••
Nu se recomandă	•
Nu este adecvat	-

•• Potrivit pentru utilizare în interior și în exterior
 •••/•• Foarte potrivit pentru interior / Potrivit pentru exterior