

Pararoom Primer

1/1

DESCRIPTION

PARAROOM PRIMER is a water based milky liquid, which is transparent when dry. **PARAROOM PRIMER** can be applied to natural slates, synthetic slates, bricks, facing bricks, and corrugated sheets or concrete or baked earth roofing tiles.

APPLICATION

Because of its high penetrating capacity, **PARAROOM PRIMER** is used as adherence coat for **PARAROOM TILE** or **PARAROOM SUPER**. Using **PARAROOM PRIMER** considerably facilitates immediate adherence of **PARAROOM TILE** or **PARAROOM SUPER** to porous or non-porous surfaces.

METHOD OF USE

First clean the surface. After the surface has dried, apply **PARAROOM PRIMER** with roll brush or by irrigation. **PARAROOM PRIMER** dries within two hours and a transparent film forms.

PROPERTIES

Consistency	Liquid milky
Basis of the product	Water based acrylate emulsion
Density	1,00 kg/l
Quantity used	0,20 kg/m ² - 0,30 kg/m ²
Processing temperature	+5°C - +30°C

DRYING TIME

1 to 2 hours depending on atmospheric conditions and porosity of the surface.

PACKAGING

5 l – 10 l – 25 l

LIMITATION

PARAROOM PRIMER cannot be applied in case of frost or possible night frost as well as not when it is raining or in stormy weather.

CLEANING

After use clean immediately with water.

SHELF LIFE

Can be kept for 12 months in unopened container and frost free.

SAFETY

Please see our safety sheet.

042002

The data on this sheet have been drafted according to the last state of the laboratory data. Technical characteristics can be changed or adapted. We are not responsible in case of incompleteness. Before usage, one needs to ensure that the product is suitable for its application. Therefore, tests are necessary. Our general conditions apply.